

**RECOMMEND USING ANY OF THE SEALIGUP HEAVY DUTY TIRE SEALANTS (502,603,603R, 605R)**

**ALL OTR TIRES BY SIZE**

| TIRE SIZE (Metric)            | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|-------------------------------|--------------------------|----------------------------|------------------|
| <b>10" &amp; SMALLER RIMS</b> |                          |                            |                  |
|                               | 3.50-6                   | 320                        |                  |
|                               | 4.00-6                   | 370                        |                  |
|                               | 3.50-8                   | 360                        |                  |
|                               | 4.00-8                   | 430                        |                  |
|                               | 5.70/5.00-8              | 600                        |                  |
|                               | 4.00-9                   | 500                        |                  |
|                               | 6.90/6.00-9              | 820                        |                  |
|                               | 6.50-10                  | 1010                       |                  |
|                               | 7.50-10                  | 1220                       |                  |
|                               | 9.00-10                  | 1450                       |                  |

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
| <b>12" RIMS</b>    |                          |                            |                  |
|                    | 4.00-12                  | 610                        |                  |
|                    | 5.70-12                  | 450                        |                  |
|                    | 26 x 12.00-12            | 1700                       |                  |
|                    | 4.00-12                  | 590                        |                  |
|                    | 5.00-12                  | 680                        |                  |
|                    | 7.00-12                  | 1180                       |                  |
|                    | 23 x 8.50-12             | 600                        |                  |
|                    | 27 x 8.50-12             | 620                        |                  |

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
| <b>14" RIMS</b>    |                          |                            |                  |
|                    | 5-14                     | 710                        |                  |
|                    | 11L-14                   | 1880                       |                  |
|                    | 6.00-14                  | 950                        |                  |
|                    | 7.50-14                  | 1250                       |                  |
|                    | 9.5L-14                  | 1620                       |                  |
|                    | 8.5L-14                  | 1410                       |                  |
|                    | 24 x 8.50-14             | 1200                       |                  |

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
| <b>15" RIMS</b>    |                          |                            |                  |
|                    | 4.00-15                  | 640                        | 0.6              |
|                    | 5.00-15                  | 730                        | 0.7              |
|                    | 5.70-15                  | 930                        | 0.9              |
|                    | 5.90-15                  | 930                        | 0.9              |
|                    | 6.40-15                  | 1020                       | 1.0              |
|                    | 6.70-15                  | 1080                       | 1.1              |
|                    | 7.5L-15                  | 1390                       | 1.4              |
|                    | 7.50-15                  | 1630                       | 1.6              |
|                    | 7.60-15                  | 1280                       | 1.3              |
|                    | 8.25-15                  | 1860                       | 1.9              |
|                    | 9.5L-15                  | 1670                       | 1.7              |
|                    | 14.0/65-15               | 2820                       | 2.8              |
|                    | 25 x 7.50-15             | 1120                       | 1.1              |
|                    | 27 x 8.50-15             | 1330                       | 1.3              |
|                    | 7.00L15(29 x 8.0-15)     | 1380                       | 1.4              |
|                    | 7.00-15(30 x 8.0-15)     | 1380                       | 1.4              |
|                    | 27 x 9.50-15             | 1440                       | 1.4              |
|                    | 10.00-15                 | 2090                       | 2.1              |
|                    | 11.00-15                 | 2300                       | 2.3              |
|                    | 11L-15                   | 2060                       | 2.1              |

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
|                    | 12.5L-15                 | 2340                       | 2.3              |
|                    | 31 x 13.50-15            | 2540                       | 2.5              |
|                    | 31 x 15.50-15            | 2840                       | 2.8              |
|                    | 35 x 12.50-15            | 2660                       | 2.7              |
|                    | 35 x 15-15               | 3060                       | 3.1              |
|                    | 250-15                   | 380                        | 0.4              |
|                    | 300-15                   | 570                        | 0.6              |

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
| <b>16" RIMS</b>    |                          |                            |                  |
|                    | 5.50-16                  | 940                        | 0.9              |
|                    | 6.00-16                  | 1090                       | 1.1              |
|                    | 6.50-16                  | 1170                       | 1.2              |
|                    | 7.50-16                  | 1520                       | 1.5              |
|                    | 7.50/8.00-16             | 1610                       | 1.6              |
|                    | 9.00-16                  | 1830                       | 1.8              |
|                    | 9.5-16                   | 1860                       | 1.9              |
|                    | 10.00-16                 | 2250                       | 2.3              |
|                    | 11L-16                   | 2070                       | 2.1              |
|                    | 11.00-16                 | 2800                       | 2.8              |
|                    | 12.5L-16                 | 2410                       | 2.4              |
|                    | 12.5/70-16               | 2530                       | 2.5              |
|                    | 12.4-16                  | 2690                       | 2.7              |
|                    | 280/70-16                | 2690                       | 2.7              |

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
| <b>16.1" RIMS</b>  |                          |                            |                  |
|                    | 13.50-16.1               | 3250                       | 3.3              |
|                    | 14.5/75-16.1             | 3150                       | 3.2              |
|                    | 14L-16.1                 | 3220                       | 3.2              |
|                    | 16.5L-16.1               | 3940                       | 3.9              |
|                    | 18.4-16.1                | 4880                       | 4.9              |
|                    | 19.5L-16.1               | 5120                       | 5.1              |
|                    | 21.5L-16.1               | 5610                       | 5.6              |
|                    | 19L-16.1                 | 4560                       | 4.6              |
|                    | 38 x 20.00-16.1          | 4560                       | 4.6              |

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
| <b>16.5" RIMS</b>  |                          |                            |                  |
|                    | 10-16.5                  | 2120                       | 2.1              |
|                    | 12-16.5                  | 2520                       | 2.5              |

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
| <b>17.5" RIMS</b>  |                          |                            |                  |
|                    | 14-17.5                  | 3040                       | 3.0              |
|                    | 36 x 16-17.5             | 3440                       | 3.4              |

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
| <b>18" RIMS</b>    |                          |                            |                  |
|                    | 7.50-18                  | 3000                       | 3.0              |
|                    | 9.5-18                   | 2000                       | 2.0              |
|                    | 10.5/80-18               | 2200                       | 2.2              |
|                    | 12.0/12.5-18             | 2530                       | 2.5              |
|                    | 4.00-18                  | 690                        | 0.7              |
|                    | 7.50-18                  | 1640                       | 1.6              |
|                    | 12.5/65-18               | 2540                       | 2.5              |
|                    | 12.5/80-18               | 2710                       | 2.7              |
|                    | 15.0/55-18               | 2680                       | 2.7              |
|                    | 15.5/60-18               | 3350                       | 3.4              |

**FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.**

**RECOMMEND USING ANY OF THE SEALIGUP HEAVY DUTY TIRE SEALANTS (502,603,603R, 605R)**

**ALL OTR TIRES BY SIZE**

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
|                    | 15.5/70-18               | 3790                       | 3.8              |
| 280/70-18          |                          | 3030                       | 3.0              |
| <b>19" RIMS</b>    |                          |                            |                  |
|                    | 4.00-19                  | 740                        | 0.7              |
|                    | 6.00-19                  | 1260                       | 1.3              |
| <b>19.5" RIMS</b>  |                          |                            |                  |
|                    | 15.00-19.5               | 3890                       | 3.9              |
|                    | 18.00-19.5               | 4610                       | 4.6              |
|                    | 40 x 19-19.5             | 4240                       | 4.2              |
| <b>20" RIMS</b>    |                          |                            |                  |
|                    | 7.50-20                  | 1680                       | 1.7              |
|                    | 8.3-20                   | 1892                       | 1.9              |
|                    | 8.50-20                  | 2369                       | 2.4              |
|                    | 9.00-20                  | 2510                       | 2.5              |
|                    | 9.50-20                  | 2060                       | 2.1              |
|                    | 10.00-20                 | 2760                       | 2.8              |
|                    | 11.00-20                 | 3030                       | 3.0              |
|                    | 12.00-20                 | 3290                       | 3.3              |
|                    | 10/10.5-20               | 2510                       | 2.5              |
|                    | 11.25-20                 | 2690                       | 2.7              |
|                    | 12.5-20                  | 3010                       | 3.0              |
|                    | 14.00-20                 | 4630                       | 4.6              |
|                    | 16.00-20                 | 5730                       | 5.7              |
|                    | 42 x 25.00-20            | 6350                       | 6.4              |
|                    | 44 x 18.00-20            | 6990                       | 7.0              |
|                    | 48 x 25.00-20            | 7550                       | 7.6              |
|                    | 48 x 31.00-20            | 9210                       | 9.2              |
|                    | 17.5/65-20               | 4570                       | 4.6              |
| 275/80-20          |                          | 2440                       | 2.4              |
| 335/80-20          |                          | 3050                       | 3.1              |
| 365/80-20          |                          | 3470                       | 3.5              |
| 375/75-20          |                          | 2776                       | 2.8              |
| 280/70-20          |                          | 3400                       | 3.4              |
| 300/70-20          |                          | 3660                       | 3.7              |
| 360/70-20          |                          | 4580                       | 4.6              |
| 405/70-20          |                          | 4000                       | 4.0              |
| <b>21" RIMS</b>    |                          |                            |                  |
|                    | 12-21                    | 3810                       | 3.8              |
|                    | 14-21                    | 5029                       | 5.0              |
|                    | 24-21                    | 7620                       | 7.6              |
| <b>22" RIMS</b>    |                          |                            |                  |
|                    | 8.3-22                   | 1820                       | 1.8              |
|                    | 7.50-22                  | 1850                       | 1.9              |
|                    | 9.5-22                   | 2210                       | 2.2              |
| <b>22.5" RIMS</b>  |                          |                            |                  |
|                    | 13-22.5                  | 3130                       | 3.1              |
|                    | 15-22.5                  | 3860                       | 3.9              |
|                    | 18-22.5                  | 4970                       | 5.0              |

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
| 600/55-22.5        |                          | 6980                       | 7.0              |
| 700/50-22.5        |                          | 8110                       | 8.1              |
| 600/55-22.5        |                          | 6980                       | 7.0              |
| 375/65-22.5        |                          | 4106                       | 4.1              |
| <b>24" RIMS</b>    |                          |                            |                  |
|                    | 7.50-24                  | 2040                       | 2.0              |
|                    | 9.00-24                  | 2060                       | 2.1              |
|                    | 9.50-24                  | 2320                       | 2.3              |
|                    | 11.00-24                 | 3590                       | 3.6              |
|                    | 11.25-24                 | 3570                       | 3.6              |
|                    | 12.00-24                 | 3590                       | 3.6              |
|                    | 13.00-24                 | 4180                       | 4.2              |
|                    | 14.00-24                 | 5040                       | 5.0              |
|                    | 16.00-24                 | 6010                       | 6.0              |
|                    | 8.3-24                   | 1920                       | 1.9              |
|                    | 11.2-24                  | 2830                       | 2.8              |
|                    | 12.4-24                  | 3360                       | 3.4              |
|                    | 13.6-24                  | 3830                       | 3.8              |
|                    | 14.9-24                  | 4320                       | 4.3              |
|                    | 16.9-24                  | 5410                       | 5.4              |
|                    | 17.5L-24                 | 5070                       | 5.1              |
|                    | 18.4-24                  | 5890                       | 5.9              |
|                    | 19.5L-24                 | 5890                       | 5.9              |
|                    | 21L-24                   | 6740                       | 6.7              |
|                    | 48 x 20.00-24            | 232                        | 0.2              |
| 280/85-24          |                          | 2830                       | 2.8              |
| 320/85-24          |                          | 3300                       | 3.3              |
| 320/70-24          |                          | 3220                       | 3.2              |
| 340/85-24          |                          | 3770                       | 3.8              |
| 360/70-24          |                          | 3800                       | 3.8              |
| 380/85-24          |                          | 4320                       | 4.3              |
| 380/70-24          |                          | 4170                       | 4.2              |
| 385/95-24          |                          | 4900                       | 4.9              |
| 420/70-24          |                          | 4810                       | 4.8              |
| 420/85-24          |                          | 5200                       | 5.2              |
| 480/65-24          |                          | 5490                       | 5.5              |
| 540/65-24          |                          | 6370                       | 6.4              |
| <b>24.5" RIMS</b>  |                          |                            |                  |
|                    | 11.00-24.5               | 3590                       | 3.6              |
| <b>25" RIMS</b>    |                          |                            |                  |
|                    | 15.5-25                  | 4680                       | 4.7              |
|                    | 16.00-25                 | 5990                       | 6.0              |
| 445/80-25          | 17.5-25                  | 5710                       | 5.7              |
|                    | 18.00-25                 | 7970                       | 8.0              |
| 525/80-25          | 20.5-25                  | 7460                       | 7.5              |
|                    | 21.00-25                 | 8940                       | 8.9              |
|                    | 23.5-25                  | 9150                       | 9.2              |
|                    | 26.5-25                  | 11230                      | 11.2             |

**FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.**

**RECOMMEND USING ANY OF THE SEALIGUP HEAVY DUTY TIRE SEALANTS (502,603,603R, 605R)**

**ALL OTR TIRES BY SIZE**

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
|--------------------|--------------------------|----------------------------|------------------|

**25" RIMS (con't)**

|           |               |       |      |
|-----------|---------------|-------|------|
|           | 29.5-25       | 14040 | 14.0 |
|           | 54 x 37.00-25 | 12330 | 12.3 |
|           | 66 x 43.00-25 | 16250 | 16.3 |
|           | 66 x 44.00-25 | 17440 | 17.4 |
|           | 67 x 34.00-25 | 13800 | 13.8 |
|           | 66 x 43.00-25 | 16650 | 16.7 |
|           | 1050/50-25    | 16440 | 16.4 |
|           | 25/65-25      | 8660  | 8.7  |
| 385/95-25 |               | 4900  | 4.9  |
| 445/80-25 |               | 5400  | 5.4  |
| 445/95-25 |               | 5830  | 5.8  |
|           | 54 x 31.00-25 | 10080 | 10.1 |
| 650/65-25 |               | 8850  | 8.9  |

**26" RIMS**

|           |               |       |      |
|-----------|---------------|-------|------|
|           | 14.9-26       | 4590  | 4.6  |
| 420/85-26 | 16.9-26       | 5610  | 5.6  |
|           | 18.4-26       | 6200  | 6.2  |
|           | 23.1-26       | 8690  | 8.7  |
|           | 24L-26        | 8240  | 8.2  |
|           | 28L-26        | 10730 | 10.7 |
|           | 54 x 31.00-26 | 9820  | 9.8  |
|           | 57 x 31.00-26 | 10330 | 10.3 |
|           | 66 x 43.00-26 | 16650 | 16.7 |
|           | 67 x 34.00-26 | 13800 | 13.8 |

**26.5" RIMS**

|  |             |      |     |
|--|-------------|------|-----|
|  | 600/55B26.5 | 7380 | 7.4 |
|  | 700/50B26.5 | 8620 | 8.6 |

**28" RIMS**

|           |          |      |     |
|-----------|----------|------|-----|
|           | 11.2-28  | 3020 | 3.0 |
|           | 12.4-28  | 3550 | 3.6 |
|           | 11.25-28 | 3870 | 3.9 |
| 340/85-28 | 13.6-28  | 4150 | 4.2 |
| 380/85-28 | 14.9-28  | 4910 | 4.9 |
| 420/85-28 | 16.9-28  | 5910 | 5.9 |
|           | 18.4-28  | 6330 | 6.3 |
|           | 21L-28   | 7200 | 7.2 |
| 320/85-28 |          | 3610 | 3.6 |
| 340/85-28 |          | 4210 | 4.2 |
| 420/70-28 |          | 5190 | 5.2 |
| 480/65-28 |          | 5930 | 5.9 |
| 540/65-28 |          | 6840 | 6.8 |

**29" RIMS**

|  |          |       |      |
|--|----------|-------|------|
|  | 24.00-29 | 12290 | 12.3 |
|  | 26.5-29  | 11460 | 11.5 |
|  | 29.5-29  | 13730 | 13.7 |
|  | 33.25-29 | 16510 | 16.5 |
|  | 65/30-29 | 13340 | 13.3 |

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
|--------------------|--------------------------|----------------------------|------------------|

|  |           |       |      |
|--|-----------|-------|------|
|  | 775/65-29 | 12360 | 12.4 |
|  | 875/65-29 | 14550 | 14.6 |

**30" RIMS**

|           |         |      |     |
|-----------|---------|------|-----|
|           | 7.2-30  | 5050 | 5.1 |
|           | 12.4-30 | 4050 | 4.1 |
| 380/85-30 | 14.9-30 | 5050 | 5.1 |
| 420/90-30 | 16.9-30 | 6130 | 6.1 |
| 460/85-30 | 18.4-30 | 6730 | 6.7 |
|           | 23.1-30 | 9150 | 9.2 |
| 420/85-30 |         | 8890 | 8.9 |
| 540/65-30 |         | 7090 | 7.1 |

**32" RIMS**

|           |                 |       |      |
|-----------|-----------------|-------|------|
|           | 9.5-32          | 2870  | 2.9  |
|           | 24.5-32         | 10380 | 10.4 |
|           | 30.5L-32        | 13350 | 13.4 |
|           | 35.5L-32        | 16630 | 16.6 |
|           | 68 x 50.00-32   | 20410 | 20.4 |
|           | 76 x 50.00-32   | 22570 | 22.6 |
|           | 76 x 50.00B32   | 22570 | 22.6 |
|           | 78 x 45.00-32   | 21320 | 21.3 |
|           | DH 35.5L-32     | 16970 | 17.0 |
|           | DH73 x 44.00-32 | 18460 | 18.5 |
|           | VA35.5L-32      | 16840 | 16.8 |
|           | VA73 x 44.00-32 | 18910 | 18.9 |
|           | 68 x 50.00-32   | 20410 | 20.4 |
| 900/60-32 |                 | 15300 | 15.3 |

**33" RIMS**

|  |          |       |      |
|--|----------|-------|------|
|  | 18.00-33 | 8660  | 8.7  |
|  | 33.5-33  | 18020 | 18.0 |
|  | 37.5-33  | 21460 | 21.5 |
|  | 21/90-33 | 10810 | 10.8 |
|  | 35/65-33 | 17060 | 17.1 |
|  | 65/35-33 | 16560 | 16.6 |

**34" RIMS**

|           |         |       |      |
|-----------|---------|-------|------|
| 290/95-34 |         | 3870  | 3.9  |
| 320/85-34 |         | 4070  | 4.1  |
| 380/85-34 | 14.9-34 | 5450  | 5.5  |
| 460/85-34 | 18.4-34 | 7020  | 7.0  |
| 480/85-34 | 18.4-34 | 7470  | 7.5  |
| 520/85-34 | 20.8-34 | 8560  | 8.6  |
| 460/85-34 |         | 11120 | 11.1 |
| 385/85-34 |         | 5450  | 5.5  |
| 420/85-34 |         | 10170 | 10.2 |
| 480/70-34 |         | 10240 | 10.2 |
|           | 23.1-34 | 10080 | 10.1 |
| 600/65B34 |         | 9040  | 9.0  |
| 700/55B34 |         | 10490 | 10.5 |

**FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.**

**RECOMMEND USING ANY OF THE SEALIGUP HEAVY DUTY TIRE SEALANTS (502,603,603R, 605R)**

**ALL OTR TIRES BY SIZE**

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
|--------------------|--------------------------|----------------------------|------------------|

**35" RIMS**

|  |          |       |      |
|--|----------|-------|------|
|  | 21.00-35 | 11070 | 11.1 |
|  | 29.5-35  | 15050 | 15.1 |
|  | 33.25-35 | 17400 | 17.4 |
|  | 37.25-35 | 21230 | 21.2 |

**36" RIMS**

|  |         |      |     |
|--|---------|------|-----|
|  | 13.6-36 | 4720 | 4.7 |
|--|---------|------|-----|

**38" RIMS**

|           |         |       |      |
|-----------|---------|-------|------|
|           | 11.2-38 | 3780  | 3.8  |
|           | 12.4-38 | 4380  | 4.4  |
|           | 14.9-38 | 5700  | 5.7  |
|           | 15.5-38 | 5780  | 5.8  |
|           | 16.9-38 | 6770  | 6.8  |
| 480/80-38 | 18.4-38 | 7890  | 7.9  |
| 520/85-38 | 20.8-38 | 9390  | 9.4  |
| 320/85-38 |         | 4420  | 4.4  |
| 540/65-38 |         | 8070  | 8.1  |
| 600/65-38 |         | 9680  | 9.7  |
| 650/65-38 |         | 11140 | 11.1 |
| 420/85-38 |         | 11510 | 11.5 |
| 460/85-38 |         | 12540 | 12.5 |
| 480/70-38 |         | 11580 | 11.6 |
| 650/85-38 |         | 12540 | 12.5 |
| 710/70-38 |         | 15490 | 15.5 |
| 800/70-38 |         | 15170 | 15.2 |

**39" RIMS**

|  |             |       |      |
|--|-------------|-------|------|
|  | 37.5-39     | 22760 | 22.8 |
|  | 40.5/75-39  | 23750 | 23.8 |
|  | 40/65-39    | 22660 | 22.7 |
|  | 41.25/70-39 | 23880 | 23.9 |
|  | 45/65-39    | 25410 | 25.4 |
|  | 65/40-39    | 21670 | 21.7 |

**42" RIMS**

|           |         |       |      |
|-----------|---------|-------|------|
|           | 12.4-42 | 4330  | 4.3  |
| 480/80-42 | 18.4-42 | 8260  | 8.3  |
| 520/85-42 | 20.8-42 | 9920  | 9.9  |
| 320/90-42 |         | 4790  | 4.8  |
| 900/50-42 |         | 15670 | 15.7 |
| 710/70-42 |         | 17280 | 17.3 |

**45" RIMS**

|  |          |       |      |
|--|----------|-------|------|
|  | 45/65-45 | 28680 | 28.7 |
|  | 65/45-45 | 27560 | 27.6 |

| TIRE SIZE (Metric) | TIRE SIZE (Conventional) | Tire Sealant required (ML) | Tire Sealant (L) |
|--------------------|--------------------------|----------------------------|------------------|
|--------------------|--------------------------|----------------------------|------------------|

**46" RIMS**

|           |         |      |      |
|-----------|---------|------|------|
| 320/90-46 | 12.4-46 | 5080 | 5.1  |
|           | 14.9-46 | 6380 | 6.4  |
| 480/80-46 | 18.4-46 | 8660 | 8.7  |
| 320/90-46 |         | 5070 | 5.1  |
| 380/90-46 |         | 6520 | 6.6  |
| 420/80-46 |         | 7060 | 7.1  |
| 520/85-46 |         | 9990 | 10.0 |

**48" RIMS**

|           |  |      |     |
|-----------|--|------|-----|
| 230/95-48 |  | 3480 | 3.5 |
|-----------|--|------|-----|

**49" RIMS**

|  |          |       |      |
|--|----------|-------|------|
|  | 18.00-49 | 10460 | 10.5 |
|  | 27.00-49 | 18170 | 18.2 |
|  | 31/90-49 | 19080 | 19.1 |

**50" RIMS**

|            |  |      |     |
|------------|--|------|-----|
| 380/90-50  |  | 6770 | 6.8 |
| 320/90-50  |  | 5370 | 5.4 |
| 380/105-50 |  | 7650 | 7.7 |
| 480/80-50  |  | 9090 | 9.1 |

**51" RIMS**

|  |          |       |      |
|--|----------|-------|------|
|  | 30.00-51 | 22300 | 22.3 |
|  | 33.00-51 | 25530 | 25.6 |
|  | 36.00-51 | 29320 | 29.4 |
|  | 50/65-51 | 35470 | 35.5 |

**54" RIMS**

|           |  |      |     |
|-----------|--|------|-----|
| 270/95-54 |  | 5736 | 5.8 |
| 380/90-54 |  | 7170 | 7.2 |

**56.5" RIMS**

|  |         |       |      |
|--|---------|-------|------|
|  | 30-56.5 | 18200 | 18.2 |
|--|---------|-------|------|

**57" RIMS**

|  |            |       |      |
|--|------------|-------|------|
|  | 37.00-57   | 32430 | 32.5 |
|  | 40.00-57   | 36820 | 36.9 |
|  | 49.5-57    | 42770 | 42.8 |
|  | 46/90-57   | 37350 | 37.4 |
|  | 49.5/85-57 | 45840 | 45.9 |
|  | 50/80-57   | 43580 | 43.6 |
|  | 50/90-57   | 44990 | 45.0 |
|  | 53.5/85-57 | 48870 | 48.9 |
|  | 55.5/80-57 | 47910 | 48.0 |
|  | 58/85-57   | 51180 | 51.2 |
|  | 65/65-57   | 56170 | 56.2 |
|  | 70/70-57   | 64490 | 64.5 |

**63" RIMS**

|  |          |       |      |
|--|----------|-------|------|
|  | 53/80-63 | 53110 | 53.2 |
|  | 55/80-63 | 59210 | 59.3 |
|  | 59/80-63 | 63100 | 63.1 |

**FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.**