

**RECOMMEND USING ANY OF THE SEALIGUP HEAVY DUTY TIRE SEALANTS (502,603,603R, 605R)**

**ALL OTR TIRES BY SIZE**

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
--------------------	--------------------------	-----------------------------	---------------------

**10" & SMALLER RIMS**

	3.50-6	11	
	4.00-6	13	
	3.50-8	12	
	4.00-8	15	
	5.70/5.00-8	21	
	4.00-9	17	
	6.90/6.00-9	28	
	6.50-10	34	
	7.50-10	41	
	9.00-10	49	

**12" RIMS**

	4.00-12	21	
	5.70-12	15	
	26 x 12.00-12	58	
	4.00-12	20	
	5.00-12	23	
	7.00-12	40	
	23 x 8.50-12	21	
	27 x 8.50-12	21	

**14" RIMS**

	5-14	24	
	11L-14	64	
	6.00-14	32	
	7.50-14	42	
	9.5L-14	55	
	8.5L-14	48	
	24 x 8.50-14	41	

**15" RIMS**

	4.00-15	22	
	5.00-15	25	
	5.70-15	31	
	5.90-15	32	
	6.40-15	34	
	6.70-15	37	
	7.5L-15	47	
	7.50-15	56	
	7.60-15	44	
	8.25-15	63	
	9.5L-15	57	
	14.0/65-15	96	
	25 x 7.50-15	38	
	27 x 8.50-15	45	
	7.00L15(29 x 8.0-15)	47	
	7.00-15(30 x 8.0-15)	47	
	27 x 9.50-15	49	
	10.00-15	71	
	11.00-15	78	
	11L-15	70	
	15.5/70-18	129	1.1
280/70-18		103	0.9

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
--------------------	--------------------------	-----------------------------	---------------------

	12.5L-15	79	0.7
	31 x 13.50-15	86	0.7
	31 x 15.50-15	96	0.8
	35 x 12.50-15	90	0.8
	35 x 15-15	104	0.9
	250-15	64	0.5
	300-15	96	0.8

**16" RIMS**

	5.50-16	32	0.3
	6.00-16	37	0.3
	6.50-16	40	0.4
	7.50-16	52	0.5
	7.50/8.00-16	55	0.5
	9.00-16	62	0.5
	9.5-16	63	0.5
	10.00-16	77	0.7
	11L-16	70	0.6
	11.00-16	95	0.8
	12.5L-16	82	0.7
	12.5/70-16	86	0.7
	12.4-16	91	0.8
280/70-16		91	0.8

**16.1" RIMS**

	13.50-16.1	110	0.9
	14.5/75-16.1	107	0.9
	14L-16.1	109	0.9
	16.5L-16.1	134	1.1
	18.4-16.1	165	1.3
	19.5L-16.1	174	1.4
	21.5L-16.1	190	1.5
	19L-16.1	154	1.3
	38 x 20.00-16.1	154	1.3

**16.5" RIMS**

	10-16.5	72	0.6
	12-16.5	86	0.7

**17.5" RIMS**

	14-17.5	103	0.9
	36 x 16-17.5	117	1.0

**18" RIMS**

	7.50-18	102	0.8
	9.5-18	68	0.6
	10.5/80-18	75	0.6
	12.0/12.5-18	86	0.7
	4.00-18	24	0.2
	7.50-18	56	0.5
	12.5/65-18	86	0.7
	12.5/80-18	92	0.8
	15.0/55-18	91	0.8
	15.5/60-18	114	0.9
600/55-22.5		236	1.9
700/50-22.5		274	2.2

**FOR USE IN TUBELESS TIRES WITH DELTA FIRST'S LINE OF SEALIGUP TIRE SEALANTS. FOR TUBES CONSULT SPECIAL DOSAGE CHARTS. FOR OTHER TYPES OF TIRES, SEE SEPARATE APPLICATION CHARTS.**

**RECOMMEND USING ANY OF THE SEALIGUP HEAVY DUTY TIRE SEALANTS (502,603,603R, 605R)**

**ALL OTR TIRES BY SIZE**

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
--------------------	--------------------------	-----------------------------	---------------------

**19" RIMS**

	4.00-19	25	0.2
	6.00-19	43	0.3

**19.5" RIMS**

	15.00-19.5	132	1.0
	18.00-19.5	156	1.2
	40 x 19-19.5	144	1.1

**20" RIMS**

	7.50-20	57	0.5
	8.3-20	65	0.6
	8.50-20	81	0.7
	9.00-20	85	0.7
	9.50-20	70	0.6
	10.00-20	94	0.8
	11.00-20	103	0.9
	12.00-20	112	0.9
	10/10.5-20	85	0.7
	11.25-20	91	0.8
	12.5-20	102	0.8
	14.00-20	157	1.3
	16.00-20	194	1.6
	42 x 25.00-20	215	1.7
	44 x 18.00-20	237	1.9
	48 x 25.00-20	255	2.0
	48 x 31.00-20	312	2.5
	17.5/65-20	155	1.3
275/80-20		82	0.7
335/80-20		103	0.9
365/80-20		118	1.0
375/75-20		94	0.8
280/70-20		115	0.9
300/70-20		124	1.0
360/70-20		155	1.3
405/70-20		136	1.1

**21" RIMS**

	12-21	129	1.1
	14-21	170	1.4
	24-21	258	2.1

**22" RIMS**

	8.3-22	62	0.5
	7.50-22	63	0.5
	9.5-22	75	0.6

**22.5" RIMS**

	13-22.5	106	0.9
	15-22.5	131	1.1
	18-22.5	168	1.4

**25" RIMS (con't)**

	29.5-25	475	3.8
	54 x 37.00-25	417	3.3
	66 x 43.00-25	550	4.3

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
--------------------	--------------------------	-----------------------------	---------------------

600/55-22.5		236	1.9
375/65-22.5		139	1.1

**24" RIMS**

	7.50-24	69	0.6
	9.00-24	70	0.6
	9.50-24	79	0.7
	11.00-24	122	1.0
	11.25-24	121	1.0
	12.00-24	122	1.0
	13.00-24	142	1.2
	14.00-24	171	1.4
	16.00-24	204	1.6
	8.3-24	65	0.6
	11.2-24	96	0.8
	12.4-24	114	0.9
	13.6-24	130	1.1
	14.9-24	147	1.2
	16.9-24	183	1.5
	17.5L-24	172	1.4
	18.4-24	200	1.6
	19.5L-24	200	1.6
	21L-24	228	1.8
	48 x 20.00-24	232	1.9
280/85-24		96	0.8
320/85-24		112	0.9
320/70-24		109	0.9
340/85-24		128	1.0
360/70-24		129	1.1
380/85-24		147	1.2
380/70-24		141	1.2
385/95-24		166	1.3
420/70-24		163	1.3
420/85-24		176	1.4
480/65-24		186	1.5
540/65-24		216	1.7

**24.5" RIMS**

	11.00-24.5	122	1.0
--	------------	-----	-----

**25" RIMS**

	15.5-25	158	1.3
	16.00-25	203	1.6
445/80-25	17.5-25	193	1.6
	18.00-25	270	2.2
525/80-25	20.5-25	253	2.0
	21.00-25	303	2.4
	23.5-25	310	2.5
	26.5-25	380	3.0

	775/65-29	418	3.3
	875/65-29	492	3.9

**30" RIMS**

	7.2-30	171	1.4
--	--------	-----	-----

**FOR USE IN TUBELESS TIRES WITH DELTA FIRST'S LINE OF SEALIGUP TIRE SEALANTS. FOR TUBES CONSULT SPECIAL DOSAGE CHARTS. FOR OTHER TYPES OF TIRES, SEE SEPARATE APPLICATION CHARTS.**

**RECOMMEND USING ANY OF THE SEALIGUP HEAVY DUTY TIRE SEALANTS (502,603,603R, 605R)**

**ALL OTR TIRES BY SIZE**

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
	66 x 44.00-25	590	4.7
	67 x 34.00-25	467	3.7
	66 x 43.00-25	563	4.4
	1050/50-25	556	4.4
	25/65-25	293	2.3
385/95-25		166	1.3
445/80-25		183	1.5
445/95-25		198	1.6
	54 x 31.00-25	341	2.7
650/65-25		300	2.4

**26" RIMS**

	14.9-26	156	1.3
420/85-26	16.9-26	190	1.5
	18.4-26	210	1.7
	23.1-26	294	2.3
	24L-26	279	2.2
	28L-26	363	2.9
	54 x 31.00-26	332	2.6
	57 x 31.00-26	350	2.8
	66 x 43.00-26	563	4.4
	67 x 34.00-26	467	3.7

**26.5" RIMS**

	600/55B26.5	250	2.0
	700/50B26.5	292	2.3

**28" RIMS**

	11.2-28	102	0.8
	12.4-28	120	1.0
	11.25-28	131	1.1
340/85-28	13.6-28	141	1.2
380/85-28	14.9-28	166	1.3
420/85-28	16.9-28	200	1.6
	18.4-28	214	1.7
	21L-28	244	2.0
320/85-28		123	1.0
340/85-28		143	1.2
420/70-28		176	1.4
480/65-28		201	1.6
540/65-28		232	1.9

**29" RIMS**

	24.00-29	416	3.3
	26.5-29	388	3.1
	29.5-29	465	3.7
	33.25-29	558	4.4
	65/30-29	451	3.6

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
	12.4-30	137	1.1
380/85-30	14.9-30	171	1.4
420/90-30	16.9-30	208	1.7
460/85-30	18.4-30	228	1.8
	23.1-30	310	2.5
420/85-30		301	2.4
540/65-30		240	1.9

**32" RIMS**

	9.5-32	97	0.8
	24.5-32	351	2.8
	30.5L-32	452	3.6
	35.5L-32	563	4.4
	68 x 50.00-32	690	5.4
	76 x 50.00-32	764	6.0
	76 x 50.00B32	764	6.0
	78 x 45.00-32	721	5.7
	DH 35.5L-32	574	4.5
	DH73 x 44.00-32	625	4.9
	VA35.5L-32	570	4.5
	VA73 x 44.00-32	640	5.0
	68 x 50.00-32	690	5.4
900/60-32		518	4.1

**33" RIMS**

	18.00-33	293	2.3
	33.5-33	610	4.8
	37.5-33	726	5.7
	21/90-33	366	2.9
	35/65-33	577	4.6
	65/35-33	560	4.4

**34" RIMS**

290/95-34		131	1.1
320/85-34		138	1.1
380/85-34	14.9-34	185	1.5
460/85-34	18.4-34	238	1.9
480/85-34	18.4-34	253	2.0
520/85-34	20.8-34	290	2.3
460/85-34		376	3.0
385/85-34		185	1.5
420/85-34		344	2.7
480/70-34		346	2.8
	23.1-34	341	2.7
600/65B34		306	2.4
700/55B34		355	2.8

**FOR USE IN TUBELESS TIRES WITH DELTA FIRST'S LINE OF SEALIGUP TIRE SEALANTS. FOR TUBES CONSULT SPECIAL DOSAGE CHARTS. FOR OTHER TYPES OF TIRES, SEE SEPARATE APPLICATION CHARTS.**

**RECOMMEND USING ANY OF THE SEALIGUP HEAVY DUTY TIRE SEALANTS (502,603,603R, 605R)**

**ALL OTR TIRES BY SIZE**

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
--------------------	--------------------------	-----------------------------	---------------------

**35" RIMS**

	21.00-35	375	3.0
	29.5-35	509	4.0
	33.25-35	589	4.7
	37.25-35	718	5.7

**36" RIMS**

	13.6-36	160	1.3
--	---------	-----	-----

**38" RIMS**

	11.2-38	128	1.0
	12.4-38	148	1.2
	14.9-38	193	1.6
	15.5-38	196	1.6
	16.9-38	229	1.8
480/80-38	18.4-38	267	2.1
520/85-38	20.8-38	318	2.5
320/85-38		150	1.2
540/65-38		273	2.2
600/65-38		328	2.6
650/65-38		377	3.0
420/85-38		389	3.1
460/85-38		424	3.4
480/70-38		392	3.1
650/85-38		424	3.4
710/70-38		524	4.1
800/70-38		513	4.1

**39" RIMS**

	37.5-39	770	6.1
	40.5/75-39	803	6.3
	40/65-39	767	6.0
	41.25/70-39	808	6.4
	45/65-39	860	6.8
	65/40-39	733	5.8

**42" RIMS**

	12.4-42	147	1.2
480/80-42	18.4-42	280	2.2
520/85-42	20.8-42	336	2.7
320/90-42		162	1.3
900/50-42		530	4.2
710/70-42		585	4.6

**45" RIMS**

	45/65-45	970	7.6
	65/45-45	932	7.3

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
--------------------	--------------------------	-----------------------------	---------------------

**46" RIMS**

320/90-46	12.4-46	172	1.4
	14.9-46	216	1.7
480/80-46	18.4-46	293	2.3
320/90-46		172	1.4
380/90-46		221	1.8
420/80-46		239	1.9
520/85-46		338	2.7

**48" RIMS**

230/95-48		118	1.0
-----------	--	-----	-----

**49" RIMS**

	18.00-49	354	2.8
	27.00-49	615	4.9
	31/90-49	646	5.1

**50" RIMS**

380/90-50		229	1.8
320/90-50		182	1.5
380/105-50		259	2.1
480/80-50		308	2.5

**51" RIMS**

	30.00-51	754	5.9
	33.00-51	864	6.8
	36.00-51	992	7.8
	50/65-51	1200	9.4

**54" RIMS**

270/95-54		194	1.6
380/90-54		243	1.9

**56.5" RIMS**

	30-56.5	616	4.9
--	---------	-----	-----

**57" RIMS**

	37.00-57	1097	8.6
	40.00-57	1245	9.8
	49.5-57	1447	11.4
	46/90-57	1263	9.9
	49.5/85-57	1550	12.2
	50/80-57	1474	11.6
	50/90-57	1522	11.9
	53.5/85-57	1653	13.0
	55.5/80-57	1620	12.7
	58/85-57	1731	13.6
	65/65-57	1900	14.9
	70/70-57	2181	17.1

**63" RIMS**

	53/80-63	1796	14.1
	55/80-63	2002	15.7
	59/80-63	2134	16.7

**FOR USE IN TUBELESS TIRES WITH DELTA FIRST'S LINE OF SEALIGUP TIRE SEALANTS. FOR TUBES CONSULT SPECIAL DOSAGE CHARTS. FOR OTHER TYPES OF TIRES, SEE SEPARATE APPLICATION CHARTS.**