

**RECOMMEND USING ANY OF THE SEALIGUP HEAVY DUTY TIRE SEALANTS
(502,603,603R, 605R)**

CONSTRUCTION & MINING OTR TIRES BY SIZE

Tire Size	Tire Sealant required (ML)	Tire Sealant (L)
15" RIMS		
7.50-15	1630	1.7
14.0/65-15	2820	2.9
35 x 15-15	3060	3.1
16" RIMS		
12.5/70-16	2530	2.6
18" RIMS		
12.5/65-18	2540	2.6
15.5/60-18	3350	3.4
15.5/70-18	3790	3.8
20" RIMS		
9.00-20	2510	2.6
10.00-20	2760	2.8
11.00-20	3030	3.1
12.00-20	3290	3.3
16.00-20	5730	5.8
17.5/65-20	4570	4.6
335/80-20	3050	3.1
365/80-20	3470	3.5
405/70-20	4000	4.0
21" RIMS		
24-21	7620	7.7
24" RIMS		
12.00-24	3590	3.6
13.00-24	4180	4.2
14.00-24	5040	5.1
16.00-24	6010	6.1
385/95-24	4900	4.9
25" RIMS		
15.5-25	4680	4.7
16.00-25	5990	6.0
17.5-25	5710	5.8
18.00-25	7970	8.0
20.5-25	7460	7.5
21.00-25	8940	9.0
23.5-25	9150	9.2
26.5-25	11230	11.3
29.5-25	14040	14.1
25/65-25	8660	8.7
385/95-25	4900	4.9
445/80-25	5400	5.4
445/95-25	5830	5.9
650/65-25	8850	8.9
29" RIMS		
29.5-29	13730	13.8
33.25-29	16510	16.6
775/65-29	12360	12.4
875/65-29	14550	14.6

Tire Size	Tire Sealant required (ML)	Tire Sealant (L)
33" RIMS		
18.00-33	8660	8.7
33.5-33	18020	18.1
37.5-33	21460	21.5
21/90-33	10810	10.9
35/65-33	17060	17.1
65/35-33	16560	16.6
35" RIMS		
21.00-35	11070	11.1
29.5-35	15050	15.1
33.25-35	17400	17.4
37.25-35	21230	21.3
39" RIMS		
37.5-39	22760	22.8
40.5/75-39	23750	23.8
40/65-39	22660	22.7
41.25/70-39	23880	23.9
45/65-39	25410	25.5
65/40-39	21670	21.7
45" RIMS		
45/65-45	28680	28.7
65/45-45	27560	27.6
49" RIMS		
18.00-49	10460	10.5
27.00-49	18170	18.2
31/90-49	19080	19.1
51" RIMS		
30.00-51	22300	22.3
33.00-51	25530	25.6
36.00-51	29320	29.4
50/65-51	35470	35.5
56.5" RIMS		
30-56.5	18200	18.2
57" RIMS		
37.00-57	32430	32.5
40.00-57	36820	36.9
49.5-57	42770	42.8
46/90-57	37350	37.4
49.5/85-57	45840	45.9
50/80-57	43580	43.6
50/90-57	44990	45.0
53.5/85-57	48870	48.9
55.5/80-57	47910	48.0
58/85-57	51180	51.2
65/65-57	56170	56.2
70/70-57	64490	64.5
63" RIMS		
53/80-63	53110	53.2

FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.

CONSTRUCTION & MINING OTR TIRES BY SIZE

Tire Size	Tire Sealant required (ML)	Tire Sealant (L)	Tire Size	Tire Sealant required (ML)	Tire Sealant (L)
			55/80-63	59210	59.3
			59/80-63	63100	63.1

FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.



**FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE
DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.**

**FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE
DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.**