

**RECOMMEND USING ANY OF THE SEALIGUP HEAVY DUTY TIRE SEALANTS
(502,603,603R, 605R)**

CONSTRUCTION & MINING OTR TIRES BY SIZE

Tire Size	Tire Sealant required (Ozs)	Tire Sealant (Gals)	Tire Size	Tire Sealant required (Ozs)	Tire Sealant (Gals)
15" RIMS			33" RIMS		
7.50-15	56	0.5	18.00-33	293	2.3
14.0/65-15	96	0.8	33.5-33	610	4.8
35 x 15-15	104	0.9	37.5-33	726	5.7
16" RIMS			21/90-33	366	2.9
12.5/70-16	86	0.7	35/65-33	577	4.6
18" RIMS			65/35-33	560	4.4
12.5/65-18	86	0.7	35" RIMS		
15.5/60-18	114	0.9	21.00-35	375	3.0
15.5/70-18	129	1.1	29.5-35	509	4.0
20" RIMS			33.25-35	589	4.7
9.00-20	85	0.7	37.25-35	718	5.7
10.00-20	94	0.8	39" RIMS		
11.00-20	103	0.9	37.5-39	770	6.1
12.00-20	112	0.9	40.5/75-39	803	6.3
16.00-20	194	1.6	40/65-39	767	6.0
17.5/65-20	155	1.3	41.25/70-39	808	6.4
335/80-20	103	0.9	45/65-39	860	6.8
365/80-20	118	1.0	65/40-39	733	5.8
405/70-20	136	1.1	45" RIMS		
21" RIMS			45/65-45	970	7.6
24-21	258	2.1	65/45-45	932	7.3
24" RIMS			49" RIMS		
12.00-24	122	1.0	18.00-49	354	2.8
13.00-24	142	1.2	27.00-49	615	4.9
14.00-24	171	1.4	31/90-49	646	5.1
16.00-24	204	1.6	51" RIMS		
385/95-24	166	1.3	30.00-51	754	5.9
25" RIMS			33.00-51	864	6.8
15.5-25	158	1.3	36.00-51	992	7.8
16.00-25	203	1.6	50/65-51	1200	9.4
17.5-25	193	1.6	56.5" RIMS		
18.00-25	270	2.2	30-56.5	616	4.9
20.5-25	253	2.0	57" RIMS		
21.00-25	303	2.4	37.00-57	1097	8.6
23.5-25	310	2.5	40.00-57	1245	9.8
26.5-25	380	3.0	49.5-57	1447	11.4
29.5-25	475	3.8	46/90-57	1263	9.9
25/65-25	293	2.3	49.5/85-57	1550	12.2
385/95-25	166	1.3	50/80-57	1474	11.6
445/80-25	183	1.5	50/90-57	1522	11.9
445/95-25	198	1.6	53.5/85-57	1653	13.0
650/65-25	300	2.4	55.5/80-57	1620	12.7
29" RIMS			58/85-57	1731	13.6
29.5-29	465	3.7	65/65-57	1900	14.9
33.25-29	558	4.4	70/70-57	2181	17.1
775/65-29	418	3.3	63" RIMS		
875/65-29	492	3.9	53/80-63	1796	14.1
			55/80-63	2002	15.7

FOR USE IN TUBELESS TIRES WITH DELTA FIRST'S LINE OF SEALIGUP TIRE SEALANTS. FOR TUBES CONSULT SPECIAL DOSAGE CHARTS. FOR OTHER TYPES OF TIRES, SEE SEPARATE APPLICATION CHARTS.

CONSTRUCTION & MINING OTR TIRES BY SIZE						
Tire Size	Tire Sealant required (Ozs)	Tire Sealant (Gals)		Tire Size	Tire Sealant required (Ozs)	Tire Sealant (Gals)
				59/80-63	2134	16.7

FOR USE IN TUBELESS TIRES WITH DELTA FIRST'S LINE OF *SEALIGUP* TIRE SEALANTS. FOR TUBES CONSULT SPECIAL DOSAGE CHARTS. FOR OTHER TYPES OF TIRES, SEE SEPARATE APPLICATION CHARTS.



**FOR USE IN TUBELESS TIRES WITH DELTA FIRST'S LINE OF ~~SEALIGUP~~ TIRE SEALANTS. FOR TUBES
CONSULT SPECIAL DOSAGE CHARTS. FOR OTHER TYPES OF TIRES, SEE SEPARATE APPLICATION
CHARTS.**

Copyright Delta First (Rev. 2011-04)

**FOR USE IN TUBELESS TIRES WITH DELTA FIRST'S LINE OF ~~SEALIGUP~~ TIRE SEALANTS. FOR TUBES
CONSULT SPECIAL DOSAGE CHARTS. FOR OTHER TYPES OF TIRES, SEE SEPARATE APPLICATION
CHARTS.**