

DELTA FIRST CORPORATION

Dedicated To Producing Quality Products For 20+ Years!

105 Bucknell Court, Suite B Atlanta, GA 30336
404-349-2560 • WATS 800-982-2325
Fax 404-349-7066

HIGH SPEED TIRE SEALANT APPLICATION CHART

FOR USE WITH SealitUp[®] Hi-Speed TIRE SEALANT

HEAVY DUTY TRUCK TIRES

All 17.5", 19.5", and 20" up to 10-20	24 oz
All 20" 11-20 and larger, All 22.5" and 24.5" regular tread	36 oz
15-22.5 and 18-22.5	48 oz

PASSENGER CARS & LIGHT TRUCKS

All 13" Tires	10 oz
All 14" and Regular Tread 15" Tires	12 oz
Wide Tread (Low Profile) 15" and ALL 16" Tires	16 oz
All Large Pickup and SUV Tires	20 oz

LOW-PROFILE TRUCK TIRES (65 OR LESS) & BUS TIRES

All 19.5" Low Profile (65 or lower)	36 oz
All 22.5" and 24.5" Low Profile (65 or lower)	48 oz
All 20.5" Tires	64 oz

RV & MOTOR HOME

All Special MH Tires	24 oz
19.5" RV Tires	36 oz
22.5" RV Tires	48 oz
24.5" RV Tires	48 oz



For Additional Information Visit www.deltafirst.com