

RECOMMEND USING SEALITUP HI SPEED (605) OR PREMIUM HEAVY DUTY COLD WEATHER (605R) SEALANT

MOTORCYCLE & SCOOTER TIRES

| TIRE SIZE | Tire Sealant required (ML) |
|-----------|----------------------------|
|-----------|----------------------------|

6" Rims

| | |
|----------|-----|
| 130/90-6 | 250 |
| 145/70-6 | 250 |
| 5.4-6 | 310 |

8" Rims

| | |
|----------|-----|
| 70/100-8 | 120 |
| 3.00-8 | 160 |
| 3.50-8 | 190 |
| 4.00-8 | 230 |

10" Rims

| | |
|-----------|-----|
| 80/100-10 | 160 |
| 90/100-10 | 190 |
| 80/90-10 | 160 |
| 90/90-10 | 190 |
| 100/90-10 | 210 |
| 110/90-10 | 240 |
| 120/90-10 | 280 |
| 130/90-10 | 310 |
| 90/80-10 | 180 |
| 110/80-10 | 230 |
| 120/80-10 | 260 |
| 2.50-10 | 150 |
| 2.75-10 | 170 |
| 3.00-10 | 180 |
| 3.50-10 | 220 |
| 4.00-10 | 260 |
| 5.4-10 | 380 |
| 6.7-10 | 520 |

12" Rims

| | |
|------------|-----|
| 80/100-12 | 180 |
| 110/100-12 | 280 |
| 90/90-12 | 210 |
| 100/90-12 | 240 |
| 110/90-12 | 270 |
| 120/80-12 | 290 |
| 130/70-12 | 310 |
| 2.75-12 | 190 |
| 3.00-12 | 200 |
| 4.00-12 | 290 |
| 4.50-12 | 330 |
| 6.7-12 | 560 |

| TIRE SIZE | Tire Sealant required (ML) |
|-----------|----------------------------|
|-----------|----------------------------|

14" Rims

| | |
|-----------|-----|
| 90/100-14 | 240 |
| 90/90-14 | 230 |
| 180/80-14 | 560 |
| 2.25-14 | 170 |
| 2.50-14 | 190 |
| 2.75-14 | 220 |
| 3.00-14 | 240 |
| 3.60-14 | 310 |
| 5.4-14 | 550 |

15" Rims

| | |
|-----------|-----|
| 130/90-15 | 390 |
| 140/90-15 | 430 |
| 150/90-15 | 480 |
| 140/80-15 | 410 |
| 150/80-15 | 450 |
| 160/80-15 | 500 |
| 170/80-15 | 540 |
| 140/70-15 | 390 |
| 2.50-15 | 190 |
| 2.75-15 | 210 |
| U90-15 | 430 |
| V90-15 | 480 |
| V85-15 | 460 |

16" Rims

| | |
|-----------|-----|
| 80/100-16 | 220 |
| 90/100-16 | 260 |
| 80/90-16 | 220 |
| 90/90-16 | 250 |
| 100/90-16 | 290 |
| 110/90-16 | 330 |
| 120/90-16 | 360 |
| 130/90-16 | 410 |
| 140/90-16 | 450 |
| 100/80-16 | 280 |
| 110/80-16 | 310 |
| 120/80-16 | 350 |
| 130/80-16 | 390 |
| 140/80-16 | 430 |
| 150/80-16 | 470 |
| 160/80-16 | 520 |
| 120/70-16 | 340 |

| TIRE SIZE | Tire Sealant required (ML) |
|-----------|----------------------------|
|-----------|----------------------------|

| | |
|-----------|-----|
| 130/70-16 | 370 |
| 180/70-16 | 580 |
| 2.00-16 | 160 |
| 2.25-16 | 180 |
| 2.50-16 | 210 |
| 2.75-16 | 240 |
| 3.00-16 | 260 |
| 3.50-16 | 320 |
| 4.60-16 | 470 |
| T90-16 | 410 |
| U90-16 | 450 |
| R85-16 | 360 |

17" Rims

| | |
|------------|-----|
| 70/100-17 | 200 |
| 100/100-17 | 310 |
| 110/100-17 | 350 |
| 80/90-17 | 230 |
| 90/90-17 | 260 |
| 100/90-17 | 300 |
| 110/90-17 | 340 |
| 120/90-17 | 380 |
| 130/90-17 | 420 |
| 90/80-17 | 250 |
| 100/80-17 | 290 |
| 110/80-17 | 330 |
| 120/80-17 | 370 |
| 130/80-17 | 410 |
| 140/80-17 | 450 |
| 150/80-17 | 490 |
| 100/70-17 | 280 |
| 110/70-17 | 320 |
| 120/70-17 | 350 |
| 130/70-17 | 390 |
| 140/70-17 | 430 |
| 150/70-17 | 470 |
| 160/70-17 | 510 |
| 120/60-17 | 340 |
| 130/60-17 | 370 |
| 140/60-17 | 410 |
| 150/60-17 | 450 |
| 160/60-17 | 490 |
| 170/60-17 | 530 |

FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALITUP TUBE SEALANT.

RECOMMEND USING SEALITUP HI SPEED (605) OR PREMIUM HEAVY DUTY COLD WEATHER (605R) SEALANT

MOTORCYCLE & SCOOTER TIRES

| TIRE SIZE | Tire Sealant required (ML) | TIRE SIZE | Tire Sealant required (ML) | TIRE SIZE | Tire Sealant required (ML) |
|-------------------------|----------------------------|-------------------------|----------------------------|-----------------|----------------------------|
| 17" Rims (con't) | | 18" Rims (con't) | | 19" Rims | |
| 160/55-17 | 470 | 120/70-18 | 370 | 70/100-19 | 210 |
| 170/55-17 | 510 | 130/70-18 | 410 | 90/100-19 | 290 |
| 180/55-17 | 550 | 140/70-18 | 450 | 100/100-19 | 330 |
| 180/50-17 | 540 | 150/70-18 | 490 | 110/100-19 | 380 |
| 190/50-17 | 570 | 160/70-18 | 530 | 70/90-19 | 210 |
| 2.00-17 | 170 | 130/60-18 | 390 | 90/90-19 | 280 |
| 2.25-17 | 190 | 140/60-18 | 430 | 100/90-19 | 320 |
| 2.50-17 | 210 | 150/60-18 | 470 | 110/90-19 | 370 |
| 2.75-17 | 240 | 160/60-18 | 510 | 120/90-19 | 410 |
| 3.00-17 | 260 | 170/60-18 | 550 | 110/80-19 | 350 |
| 3.25-17 | 280 | 180/55-18 | 570 | 2.00-19 | 180 |
| 3.50-17 | 310 | 180/50-18 | 560 | 2.50-19 | 240 |
| 4.50-17 | 410 | 2.25-18 | 230 | 2.75-19 | 270 |
| 4.60-17 | 420 | 2.50-18 | 250 | 3.00-19 | 300 |
| 5.00-17 | 470 | 2.75-18 | 270 | 3.25-19 | 330 |
| 5.10-17 | 480 | 3.00-18 | 290 | 3.50-19 | 360 |
| S90-17 | 400 | 3.25-18 | 310 | 3.60-19 | 380 |
| T90-17 | 420 | 3.50-18 | 340 | 4.10-19 | 450 |
| 18" Rims | | 3.60-18 | 350 | J90-19 | 280 |
| 90/100-18 | 280 | 4.00-18 | 390 | L90-19 | 300 |
| 100/100-18 | 320 | 4.10-18 | 420 | M90-19 | 320 |
| 110/100-18 | 360 | 4.25-18 | 440 | 21" Rims | |
| 120/100-18 | 410 | 4.50-18 | 480 | 70/100-21 | 230 |
| 90/90-18 | 270 | 4.60-18 | 390 | 80/100-21 | 270 |
| 100/90-18 | 310 | 5.10-18 | 570 | 80/90-21 | 270 |
| 110/90-18 | 350 | J90-18 | 270 | 90/90-21 | 310 |
| 120/90-18 | 390 | L90-18 | 290 | 80/80-21 | 260 |
| 130/90-18 | 440 | M90-18 | 310 | 100/80-21 | 340 |
| 4.25/85-18 | 390 | N90-18 | 350 | 2.50-21 | 260 |
| 100/80-18 | 300 | P90-18 | 370 | 2.75-21 | 290 |
| 110/80-18 | 340 | R90-18 | 390 | 3.00-21 | 320 |
| 120/80-18 | 380 | P85-18 | 380 | 3.25-21 | 350 |
| 130/80-18 | 420 | S85-18 | 410 | H90-21 | 270 |
| 140/80-18 | 460 | T85-18 | 430 | 23" Rims | |
| 150/80-18 | 510 | T80-18 | 420 | 3.00-23 | 340 |

FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALITUP TUBE SEALANT.