

RECOMMEND USING SEALIGUP HI SPEED (605) SEALANT						
MOTORCYCLE & SCOOTER TIRES						
TIRE SIZE	Tire Sealant required (Ozs)		TIRE SIZE	Tire Sealant required (Ozs)		
6" Rims			14" Rims			
130/90-6	7		90/100-14	7	130/70-16	
145/70-6	7		90/90-14	7	180/70-16	
5.4-6	9		180/80-14	15	2.00-16	
8" Rims			2.25-14	5	2.25-16	
70/100-8	4		2.50-14	5	2.50-16	
3.00-8	5		2.75-14	6	2.75-16	
3.50-8	6		3.00-14	7	3.00-16	
4.00-8	7		3.60-14	9	3.50-16	
10" Rims			5.4-14	15	4.60-16	
80/100-10	5		15" Rims		T90-16	
90/100-10	6		130/90-15	11	U90-16	
80/90-10	5		140/90-15	12	R85-16	
90/90-10	5		150/90-15	13	17" Rims	
100/90-10	6		140/80-15	11	70/100-17	6
110/90-10	7		150/80-15	13	100/100-17	9
120/90-10	8		160/80-15	14	110/100-17	10
130/90-10	9		170/80-15	15	80/90-17	6
90/80-10	5		140/70-15	11	90/90-17	7
110/80-10	7		2.50-15	5	100/90-17	8
120/80-10	7		2.75-15	6	110/90-17	9
2.50-10	4		U90-15	12	120/90-17	11
2.75-10	5		V90-15	13	130/90-17	12
3.00-10	5		V85-15	13	90/80-17	7
3.50-10	6		16" Rims		100/80-17	8
4.00-10	7		80/100-16	6	110/80-17	9
5.4-10	11		90/100-16	7	120/80-17	10
6.7-10	14		80/90-16	6	130/80-17	11
12" Rims			90/90-16	7	140/80-17	12
80/100-12	5		100/90-16	8	150/80-17	13
110/100-12	8		110/90-16	9	100/70-17	8
90/90-12	6		120/90-16	10	110/70-17	9
100/90-12	7		130/90-16	11	120/70-17	10
110/90-12	8		140/90-16	12	130/70-17	11
120/80-12	8		100/80-16	8	140/70-17	12
130/70-12	9		110/80-16	9	150/70-17	13
2.75-12	5		120/80-16	10	160/70-17	14
3.00-12	6		130/80-16	11	120/60-17	9
4.00-12	8		140/80-16	12	130/60-17	10
4.50-12	9		150/80-16	13	140/60-17	11
6.7-12	15		160/80-16	14	150/60-17	12
			120/70-16	9	160/60-17	13
					170/60-17	14

FOR USE IN TUBELESS TIRES WITH DELTA FIRST'S LINE OF SEALIGUP TIRE SEALANTS. FOR TUBES CONSULT SPECIAL DOSAGE CHARTS. FOR OTHER TYPES OF TIRES, SEE SEPARATE APPLICATION CHARTS.

