

RECOMMEND USING **SEALICUP HEAVY DUTY** OR **PREMIUM HEAVY DUTY SEALANT****CONSTRUCTION & MINING OTR TIRES BY SIZE**

Tire Size	Tire Sealant required (Ozs)	Tire Sealant (Gals)
-----------	-----------------------------	---------------------

**15" RIMS**

7.50-15	56	0.5
14.0/65-15	96	0.8
35 x 15-15	104	0.9

**16" RIMS**

12.5/70-16	86	0.7
------------	----	-----

**18" RIMS**

12.5/65-18	86	0.7
15.5/60-18	114	0.9
15.5/70-18	129	1.1

**20" RIMS**

9.00-20	85	0.7
10.00-20	94	0.8
11.00-20	103	0.9
12.00-20	112	0.9
16.00-20	194	1.6
17.5/65-20	155	1.3
335/80-20	103	0.9
365/80-20	118	1.0
405/70-20	136	1.1

**21" RIMS**

24-21	258	2.1
-------	-----	-----

**24" RIMS**

12.00-24	122	1.0
13.00-24	142	1.2
14.00-24	171	1.4
16.00-24	204	1.6
385/95-24	166	1.3

**25" RIMS**

15.5-25	158	1.3
16.00-25	203	1.6
17.5-25	193	1.6
18.00-25	270	2.2
20.5-25	253	2.0
21.00-25	303	2.4
23.5-25	310	2.5
26.5-25	380	3.0
29.5-25	475	3.8
25/65-25	293	2.3
385/95-25	166	1.3
445/80-25	183	1.5
445/95-25	198	1.6
650/65-25	300	2.4

**29" RIMS**

29.5-29	465	3.7
33.25-29	558	4.4
775/65-29	418	3.3
875/65-29	492	3.9

Tire Size	Tire Sealant required (Ozs)	Tire Sealant (Gals)
-----------	-----------------------------	---------------------

**33" RIMS**

18.00-33	293	2.3
33.5-33	610	4.8
37.5-33	726	5.7
21/90-33	366	2.9
35/65-33	577	4.6
65/35-33	560	4.4

**35" RIMS**

21.00-35	375	3.0
29.5-35	509	4.0
33.25-35	589	4.7
37.25-35	718	5.7

**39" RIMS**

37.5-39	770	6.1
40.5/75-39	803	6.3
40/65-39	767	6.0
41.25/70-39	808	6.4
45/65-39	860	6.8
65/40-39	733	5.8

**45" RIMS**

45/65-45	970	7.6
65/45-45	932	7.3

**49" RIMS**

18.00-49	354	2.8
27.00-49	615	4.9
31/90-49	646	5.1

**51" RIMS**

30.00-51	754	5.9
33.00-51	864	6.8
36.00-51	992	7.8
50/65-51	1200	9.4

**56.5" RIMS**

30-56.5	616	4.9
---------	-----	-----

**57" RIMS**

37.00-57	1097	8.6
40.00-57	1245	9.8
49.5-57	1447	11.4
46/90-57	1263	9.9
49.5/85-57	1550	12.2
50/80-57	1474	11.6
50/90-57	1522	11.9
53.5/85-57	1653	13.0
55.5/80-57	1620	12.7
58/85-57	1731	13.6
65/65-57	1900	14.9
70/70-57	2181	17.1

**63" RIMS**

53/80-63	1796	14.1
55/80-63	2002	15.7
59/80-63	2134	16.7

**FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED *SEALICUP TUBE* SEALANT.**