

DELTA FIRST CORPORATION

TUBE SEALANT APPLICATION CHART

Dedicated To Producing Quality Products For 20+ Years!

105 Bucknell Court, Suite B Atlanta, GA 30336
 404-349-2560 • WATS 800-982-2325
 Fax 404-349-7066

FOR USE WITH SealitUp® Tube SEALANT

MOTORCYCLE & SCOOTER TIRES

10" Scooter Tires	8 oz		Low Profile (80 or lower aspect ratio)	
12"-14" Tires	8 oz		12"-14" Tires	12 oz
15"-18" Tires	12 oz		15"-18" Tires	18 oz
19"-21" Tires	13 oz		19"-21" Tires	20 oz

PASSENGER CARS & LIGHT TRUCKS

All 13" Tires	10 oz
All 14" and Regular Tread 15" Tires	12 oz
Wide Tread (Low Profile) 15" and All 16" Tires	16 oz
All Large Pickup and SUV Tires	20 oz

NOTE: Tires with over 10,000 miles wear should use 2 additional ounces per tire.

HEAVY DUTY TRUCK TIRES

All 17.5", 19.5", and 20" up to 10-20	24 oz
All 20" 11-20 and larger, All 22.5" and 24.5" regular tread	36 oz
15-22.5 and 18-22.5	48 oz

RV & MOTOR HOME

All Special MH Tires	24 oz
19.5" RV Tires	36 oz
22.5" RV Tires	48 oz
24.5" RV Tires	48 oz

LOW-PROFILE TRUCK TIRES (65 OR LESS) & BUS TIRES

All 19.5" Low Profile (65 or lower)	36 oz
All 22.5" and 24.5" Low Profile (65 or lower)	48 oz
All 20.5" Tires	64 oz

For Additional Information Visit www.deltafirst.com