

**RECOMMEND USING SEALITUP HI SPEED (605) TIRE SEALANT**

**MOTORCYCLE & SCOOTER TIRES**

TIRE SIZE	Tire Sealant required (ML)	TIRE SIZE	Tire Sealant required (ML)	TIRE SIZE	Tire Sealant required (ML)
<b>6" Rims</b>		<b>14" Rims</b>		130/70-16	270
130/90-6	180	90/100-14	170	180/70-16	420
145/70-6	180	90/90-14	170	2.00-16	120
5.4-6	230	180/80-14	410	2.25-16	140
<b>8" Rims</b>		2.25-14	120	2.50-16	150
70/100-8	90	2.50-14	140	2.75-16	170
3.00-8	120	2.75-14	160	3.00-16	190
3.50-8	140	3.00-14	180	3.50-16	240
4.00-8	170	3.60-14	230	4.60-16	340
<b>10" Rims</b>		5.4-14	400	T90-16	300
80/100-10	120	<b>15" Rims</b>		U90-16	330
90/100-10	140	130/90-15	280	R85-16	260
80/90-10	120	140/90-15	310	<b>17" Rims</b>	
90/90-10	140	150/90-15	350	70/100-17	200
100/90-10	160	140/80-15	300	100/100-17	310
110/90-10	180	150/80-15	330	110/100-17	350
120/90-10	200	160/80-15	360	80/90-17	230
130/90-10	230	170/80-15	390	90/90-17	260
90/80-10	130	140/70-15	290	100/90-17	300
110/80-10	170	2.50-15	140	110/90-17	340
120/80-10	190	2.75-15	150	120/90-17	380
2.50-10	110	U90-15	310	130/90-17	420
2.75-10	120	V90-15	350	90/80-17	250
3.00-10	130	V85-15	340	100/80-17	290
3.50-10	160	<b>16" Rims</b>		110/80-17	330
4.00-10	190	80/100-16	160	120/80-17	370
5.4-10	280	90/100-16	190	130/80-17	410
6.7-10	380	80/90-16	160	140/80-17	450
<b>12" Rims</b>		90/90-16	180	150/80-17	490
80/100-12	130	100/90-16	210	100/70-17	280
110/100-12	210	110/90-16	240	110/70-17	320
90/90-12	150	120/90-16	270	120/70-17	350
100/90-12	170	130/90-16	300	130/70-17	390
110/90-12	200	140/90-16	330	140/70-17	430
120/80-12	210	100/80-16	200	150/70-17	470
130/70-12	230	110/80-16	230	160/70-17	510
2.75-12	140	120/80-16	260	120/60-17	340
3.00-12	150	130/80-16	280	130/60-17	370
4.00-12	210	140/80-16	310	140/60-17	410
4.50-12	240	150/80-16	340	150/60-17	450
6.7-12	410	160/80-16	380	160/60-17	490
		120/70-16	250	170/60-17	530

**FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALITUP TUBE SEALANT.**

**RECOMMEND USING SEALITUP HI SPEED (605) TIRE SEALANT**

**MOTORCYCLE & SCOOTER TIRES**

TIRE SIZE	Tire Sealant required (ML)	TIRE SIZE	Tire Sealant required (ML)	TIRE SIZE	Tire Sealant required (ML)
<b>17" Rims (con't)</b>		<b>18" Rims (con't)</b>		<b>19" Rims</b>	
160/55-17	340	120/70-18	270	70/100-19	210
170/55-17	370	130/70-18	300	90/100-19	290
180/55-17	400	140/70-18	320	100/100-19	330
180/50-17	390	150/70-18	350	110/100-19	380
190/50-17	420	160/70-18	390	70/90-19	210
2.00-17	130	130/60-18	280	90/90-19	280
2.25-17	140	140/60-18	310	100/90-19	320
2.50-17	160	150/60-18	340	110/90-19	370
2.75-17	170	160/60-18	370	120/90-19	410
3.00-17	190	170/60-18	400	110/80-19	350
3.25-17	210	180/55-18	420	2.00-19	180
3.50-17	220	180/50-18	410	2.50-19	240
4.50-17	300	2.25-18	170	2.75-19	270
4.60-17	310	2.50-18	180	3.00-19	300
5.00-17	340	2.75-18	190	3.25-19	330
5.10-17	350	3.00-18	210	3.50-19	360
S90-17	290	3.25-18	230	3.60-19	380
T90-17	310	3.50-18	250	4.10-19	450
<b>18" Rims</b>		3.60-18	260	J90-19	280
90/100-18	210	4.00-18	290	L90-19	300
100/100-18	230	4.10-18	300	M90-19	320
110/100-18	270	4.25-18	320	<b>21" Rims</b>	
120/100-18	300	4.50-18	350	70/100-21	230
90/90-18	200	4.60-18	280	80/100-21	270
100/90-18	230	5.10-18	420	80/90-21	270
110/90-18	260	J90-18	200	90/90-21	310
120/90-18	290	L90-18	210	80/80-21	260
130/90-18	320	M90-18	230	100/80-21	340
4.25/85-18	280	N90-18	260	2.50-21	260
100/80-18	220	P90-18	270	2.75-21	290
110/80-18	250	R90-18	290	3.00-21	320
120/80-18	280	P85-18	280	3.25-21	350
130/80-18	310	S85-18	300	H90-21	270
140/80-18	340	T85-18	310	<b>23" Rims</b>	
150/80-18	370	T80-18	310	3.00-23	340

**FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALITUP TUBE SEALANT.**